



A lubricant is recommended when using all stainless steel turnbuckles to help prevent binding.

STAINLESS STEEL TURNBUCKLES WITH LOCK NUTS

CODE	DIA MM	STYLE	LENGTH MIN	LENGTH MAX	B	L	TDL KG
*SS-311E-04	4	E & E	98	135	8		475
SS-311H-04	4	H & H	98	135	7		100
SS-311HE-04	4	H & E	98	135	8		100
SS-311E-05	5	E & E	120	170	8		680
SS-311H-05	5	H & H	120	170	7		130
SS-311HE-05	5	H & E	120	170	7		130
*SS-311J-05	5	J & J	120	170	6	10	680
*SS-311E-06	6	E & E	150	220	10		1500
SS-311H-06	6	H & H	120	220	9		350
SS-311HE-06	6	H & E	155	220	9		350
*SS-311J-06	6	J & J	150	220	7	9	1500
*SS-311E-08	8	E & E	200	280	12		2300
*SS-311H-08	8	H & H	225	280	10		650
*SS-311HE-08	8	H & E	225	280	9		650
*SS-311J-08	8	J & J	195	265	10	10	2300
*SS-311E-09	9	E & E	245	350	15	15	3100
*SS-311H-09	9	H & H	255	350	13	13	800
*SS-311HE-09	9	H & E	255	350	13	13	800
*SS-311J-09	9	J & J	235	350	10	10	3100
SS-311E-12	12	E & E	315	460	20	20	4400
SS-311H-12	12	H & H	320	460	15	15	1400
SS-311HE-12	12	H & E	320	460	14	14	1400
*SS-311J-12	12	J & J	320	455	13	13	4400
*SS-311J-14	14	J & J	315	445	16	21	6400
SS-311E-16	16	E & E	400	610	25	25	8100
*SS-311J-16	16	J & J	340	470	18	18	8100
SS-311E-19	19	E & E	500	710	30	35	11000

Legend: E = Eye
H = Hook
J = Jaw

* Available in economy range of fittings.
Please consult our sales department for pricing

TDL = TESTED DEFORATION LOAD